

| TECHNICAL DATA SHEET | DESCRIPTION                                       | DATE       |
|----------------------|---------------------------------------------------|------------|
| TDS03                | HERBISH HBV125H VINYL FLOOR DRAIN WITH 50/76MM HO | MARCH 2026 |

#### TECHNICAL DATA SHEET

Herbish® HBV vinyl floor drains are full flow floor drains, only to be used in conjunction with vinyl flooring or waterproofing membranes.

Herbish® HBV vinyl floor drains are manufactured entirely of 304ss, are corrosion resistant. Depending on Client's requirements they may be manufactured in 316ss.



**HORIZONTAL OUTLET**



**DRAIN DIMENSIONS**

|          |                     |            |
|----------|---------------------|------------|
| <b>A</b> | Flange Diameter     | 205        |
| <b>B</b> | Drain Body Diameter | 95mm       |
| <b>C</b> | Drain Height        | 130mm      |
| <b>D</b> | Outlet Diameter     | 50mm/76mm* |

(Client specification\*)

#### VINYL FLOOR DRAIN

Standard ABS water seal. \*Optional MAGdrain or Green Drain hygienic dry seal



#### BUILDING ENDURING VALUE

Tel: 011 609 3500 | Email: [marketing@polysales.com](mailto:marketing@polysales.com) | [www.polysales.com](http://www.polysales.com)  
Poly Sales House, 8B Buwbes Road North, Sebenza, 1609, South Africa. PO Box 3967, Edenvale, 1610, South Africa

Poly Sales Africa (Pty) Ltd. trading as Polysales Company Registration 2004/012256/07  
Directors: DL Coleman, P du Plessis, T Coleman

**Applications:**

Suitable vinyl floor installations

Available with a round flange

Designed for both domestic and commercial wet room design applications

Suitable for use with Polyflor sheet vinyl or other similar floor finishes

**Materials & finishes:**

Manufactured in 304 and 316 grade stainless steel

Four stylish grate options

A choice of horizontal or vertical outlets

Supplied standard with a 50mm outlet but 76mm diameter outlets are also available.

**Performance:**

Excellent corrosion resistance

Hygienic

High flow rate performance

SANS10400 compliant 75mm water seal

Supplied with strainer

No direct access to the sewer line during routine maintenance

**Installation:**

Easy to install

Tamper proof fixings for the cover are standard

Easy to clean and maintain

Locate the drain in the correct position on the floor and connect to the drainage pipework system. *Ensure the gradient/fall in the floor level is sufficient to encourage the flow of water towards the drain.* Backfill around the drain and dress floor finish up to the drain edge. Remove any protective tape/film from the unit. A mastic sealant of bead width 5-8mm is recommended around the outside of the drain top edge and floor where a good watertight seal is required between the two materials. Ensure the sealant is applied in accordance with the manufacturer's instructions.

**PLEASE NOTE:**

The off-take capacity of the drain is not only determined by the capacity of the actual drain itself, but also the waste pipe to which these elements are to be connected.

**Please adhere to the following instructions:**

The length of the waste pipeline to the vertical waste stack of the system must be as short as possible.

Avoid bends in the system where possible.

Make sure that the waste pipe has sufficient gradient for the discharge required.

If the shower drain is used for multiple showers or for showers with a higher capacity, please contact Polysales (011) 609 3500.

**Maintenance:**

All Herbish® Drainage systems stainless steel product's surfaces are finished to a satin finish. It is important to remember that such a finish can be scratched or marked by improper cleaning. While any scratches or marks may be unsightly, the corrosion resistance of your Herbish® product will not be compromised.

**Dos & Don'ts of Maintaining Herbish® Drainage Systems Products**

*Do wash frequently with water (preferably hot water) followed by rinsing with cold water. A little "Sunlight" dishwashing liquid or soap may be added to the first wash water, but too much dishwashing liquid or soap will cause "clouding" of the surface.*

*Do wash down floor drains, drainage channels and grease traps regularly. While stainless steel is generally an extremely hard metal, it will start corroding if left in contact too long with ordinary ingredients such as salt, milk, fruit juices etc.*

*Do follow the following remedial procedures when faced with the following situations:*

- *Rust Stains: Mix a solution of 1 (one) part nitric acid to 9 (nine) parts warm water (by volume), leave the solution in contact with the stained stainless steel for 1 (one) hour and then flush with cold water thoroughly.*
- *Acids: Avoid all acids at all costs. Rinse immediately with warm water, Repeat twice.*
- *Bleaches: Rinse immediately with hot soapy water.*

*Don't use "silver" cleaners.*

*Don't use chloride containing cleaning solutions. These will corrode the stainless steel.*

*Don't use scouring materials and harsh abrasives, such as steel wool and wire brushes for cleaning stainless steel. The surface responds best to the gentlest of cleaning methods. Carbon steel, if left in contact with the stainless-steel surface will rust and permanently stain your Herbish® products surface.*

*Don't use acids (especially hydrochloric acid). Tile grout removing chemicals are particularly aggressive and will pit and ultimately corrode through stainless steel if not thoroughly rinsed away.*

*Don't use "silver" cleaners.*

*Don't use chloride containing cleaning solutions. These will corrode the stainless steel.*